NILO D

MINI DOWNLIGHTS INDOOR

PROJECT INFORMATION	
Project Name	
Reference	Quantity

CODE

NID.40.R.01.CC

IP40

MADE IN ITALY

PRODUCT

FINISH

.01
White RAL 9003

TECHNICAL DRAWING





RECESSED HOLE



CODE NID.40.R.01.CC

Product	LED colour	Optic	Finish	Power
NID = NILO D	40 = 4000K	R = 70° adjustable ±15°	01 = White RAL 9003	CC = 2W

NILO D

CODE NID.40.R.01.CC

LIGHTING CHARACTERISTICS

Color Rendering Index	CRI > 90
Lumen output (source)	153 lm
Lumen output (delivered)	130 lm
Optic	70° adjustable ±15°
LED colour temperature	4000K
LED lifetime	50000h L95 B10 (Ta 25°C)
Bin selection	Binning free 2 step MacAdam's

MECHANICAL CHARACTERISTICS

Body	Anodized aluminium 6026
Finish	White RAL 9003
Installation	Fixing springs
Weight	40 g

ELECTRICAL CHARACTERISTICS

Power supply	Constant Current 500mA
Power supply cable	2x 20cm V01CN 0,2mm²
Power consumption	2W
Dimming	Dimmable

GENERAL CHARACTERISTICS

Operating temperature	-20°C ÷ +50°C
IP rating	IP40 / IP44 installed
Insulation class	Class III
Photobiological risk	RG0/RG1
Walkover	No

PHOTOMETRICS DATA

H(m/')	Ø (m/')	Lux/fc max
1.00/3.28	1,35/4.43	101/9
2.00/6.56	2,70/8.86	5/0
3.00/9.84	4,05/13.29	11/1
4.00/13.12	5,40/17.72	6/1
5.00/16.40	6,75/22.15	4/0

NILO D

CODE NID.40.R.01.CC

ACCESSORIES (Measure unit: mm)



Snoot

Art. Nr.
ACC.018

Finishes
.01 = White RAL 9003
.02 = Black RAL 9005
.16 = Flamed bronze



Honeycomb louver

Art. Nr.
ACC.122

NILO D

CODE NID.40.R.01.CC

POWER SUPPLIES

ON/OFF

Code	Input	Quantity max.	I Out	V Out	Watt	IP	Certifications
PSU.CX.003	100÷264V / 50/60 Hz	7	500mA	47V	24	IP20	CE cULus
PSU.CX.004 (500mA)	99÷264V / 50/60 Hz	6	500mA	40V	20	IP20	CE cULus

Dimmable

Code	Input	Quantity max.	I Out	V Out	Watt	IP	Certifications
PSU.CX.001_1-10V/PUSH	220÷240V / 50/60 Hz	7	500mA	47V	24	IP20	CE
PSU.CC.011_DALI-2 (DT6)	100÷240V / 50/60 Hz	6	500mA	40V	20	IP20	CE