# SLASH 30

LINEAR OUTDOOR

| PROJECT INFORMATION | |
|---|---|
| Project Name | |
| Reference | Quantity |

## CODE

**S30B.30.M.07.11.15**

IP67

MADE IN ITALY

## PRODUCT

## FINISH

**.07**
Natural anodized aluminium

## TECHNICAL DRAWING




## CODE S30B.30.M.07.11.15

| Product | LED colour | Optic | Finish | Length | Power |
|---|---|---|---|---|---|
| **S30B** = SLASH 30 | **30** = 3000K | **M** = 21° | **07** = Natural anodized aluminium | **11** = 1139mm | **15** = 15W |

# SLASH 30

## CODE S30B.30.M.07.11.15

## LIGHTING CHARACTERISTICS

| | |
|---|---|
| **Color Rendering Index** | CRI > 90 |
| **Lumen output (source)** | 1260 lm |
| **Lumen output (delivered)** | 1020 lm |
| **Optic** | 21° |
| **LED colour temperature** | 3000K |
| **LED lifetime** | 50000h L95 B10 (Ta 25°C) |
| **Bin selection** | Binning free 2 step MacAdam's |

## MECHANICAL CHARACTERISTICS

| | |
|---|---|
| **Body** | Anodized aluminium 6026 |
| **Glass** | Half frosted tempered glass 4mm |
| **Finish** | Natural anodized aluminium |
| **Installation** | Housing box / Fixing brackets |
| **Weight** | 1720 |

## ELECTRICAL CHARACTERISTICS

| | |
|---|---|
| **Power supply** | Constant voltage 24Vdc |
| **Power supply cable** | 50cm with IP68 Easy-Lock connector |
| **Power consumption** | 15W |
| **Dimming** | Dimmable |

## GENERAL CHARACTERISTICS

| | |
|---|---|
| **Operating temperature** | -20°C ÷ +50°C |
| **IP rating** | IP67 |
| **Insulation class** | Class III |
| **Photobiological risk** | RG0/RG1 |
| **Walkover** | Yes |

## PHOTOMETRICS DATA

| H(m/') | Ø (m/') | Lux/fc max |
|---|---|---|
| 1.00/3.28 | 0,35/1.15 | 8.381/779 |
| 2.00/6.56 | 0,71/2.33 | 2.095/195 |
| 3.00/9.84 | 1,06/3.48 | 931/86 |
| 4.00/13.12 | 1,41/4.63 | 523/49 |
| 5.00/16.40 | 1,76/5.77 | 335/31 |



# SLASH 30

## CODE S30B.30.M.07.11.15

## ACCESSORIES (Measure unit: mm)




Housing box
*(measure without end caps)

Art. Nr.
**HB.010**

Length
**.0282** = 282mm*
**.0568** = 568mm*
**.0853** = 853mm*
**.1139** = 1139mm*

---




Flanged housing box
*(measure without end caps)

Art. Nr.
**HB.015**

Length
**.0282** = 282mm*
**.0568** = 568mm*
**.0853** = 853mm*
**.1139** = 1139mm*

---

Anti-Glare louver

Art. Nr.
**ACC.130**

Length
**.0282** = 282mm
**.0568** = 568mm
**.0853** = 853mm
**.1139** = 1139mm

---

Transparent extra clear glass

Art. Nr.
**ACC.142**

Length
**.0282** = 282mm
**.0568** = 568mm
**.0853** = 853mm
**.1139** = 1139mm

---




Fixing bracket (couple)

Art. Nr.
**ACC.125**

Finishes
**.07** = Natural anodized aluminium

---




Housing box alignment kit

Art. Nr.
**ACC.093**

---




Housing box fixing kit

Art. Nr.
**ACC.094**

---

# SLASH 30

## CODE S30B.30.M.07.11.15

## ACCESSORIES




Fixing springs for housing box installation (couple)

Art. Nr.
**ACC.159**

Head cable 5m

Art. Nr.
**ACC.057**

Y connection cable 75cm

Art. Nr.
**ACC.058**

Extension cable 1m

Art. Nr.
**ACC.059**




Pair of extractors

Art. Nr.
**ACC.118**

# SLASH 30

## CODE S30B.30.M.07.11.15

## POWER SUPPLIES

### ON/OFF

| Code | Input | Quantity max. | I Out | V Out | Watt | IP | Certifications |
|---|---|---|---|---|---|---|---|
| PSU.CX.004 | 99÷264V / 50/60 Hz | 0 | 0,9 A | 24Vdc | 20 | IP20 | CE cULus |
| PSU.CV.005 | 90÷305V / 47/63 Hz | 1 | 1 A | 24Vdc | 25 | IP67 | CE cULus |
| PSU.CV.006 | 90÷305V / 47/63 Hz | 2 | 2,5 A | 24Vdc | 60 | IP67 | CE cULus |
| PSU.CV.007 | 90÷305V / 47/63 Hz | 3 | 3,75 A | 24Vdc | 90 | IP67 | CE cULus |
| PSU.CV.012 | 90÷305V / 47/63 Hz | 6 | 6,3 A | 24Vdc | 150 | IP67 | CE cULus |
| PSU.CV.021 | 90÷305V / 47/63 Hz | 10 | 10 A | 24Vdc | 240 | IP67 | CE cULus |

### Control gear

| Code | Input | Quantity max. | I Out | V Out | Watt | IP | Certifications |
|---|---|---|---|---|---|---|---|
| CGE.004_1-10V | 24Vdc | 12 | 12 A | 24Vdc | 288 | IP20 | CE |
| CGE.004.IP_1-10V | 24Vdc | 12 | 12 A | 24Vdc | 288 | IP67 | CE |
| CGE.017_DALI (DT6) | 24Vdc | 12 | 12 A | 24Vdc | 288 | IP20 | CE |
| CGE.017.IP_DALI (DT6) | 24Vdc | 12 | 12 A | 24Vdc | 288 | IP67 | CE |
| CGE.042_DALI-2 (DT6) | 24Vdc | 12 | 12 A | 24Vdc | 288 | IP20 | CE |
| CGE.042_TRIAC | 24Vdc | 12 | 12 A | 24Vdc | 288 | IP20 | CE |
| CGE.020_DMX | 24Vdc | 6 | 6,5 A | 24Vdc | 156 | IP20 | CE |